

»Universal« push-off bucket

- » Large transport volume
- » Loading height is higher compared to normal buckets because the loading bucket is not immersed in the trailer
- » A wide range of different material can be pushed off quickly, easily and completely with metered and controlled unloading
- » No material is left clinging and nothing falls out beside the trailer
- » Hydraulically actuated front wall which is closed by the bucket opening during travel, thereby preventing transport loss

Available on request



High loading height
Large transport volume
Metered and controlled unloading



For attachment to Euronorm

Art.no.	Width	Content approx.	Weight without front wall approx.	Qty.
ASSFLM200000	2000 mm	2.1 m ³	540 kg	Pcs.
ASSFLM240000	2400 mm	2.6 m ³	650 kg	Pcs.
ASSFLM280000	2800 mm	3.0 m ³	755 kg	Pcs.

Hydraulic front wall for push-off bucket available on request.

For attachment to wheel or telescopic loaders

Art.no.	Width	Content approx.	Weight without front wall approx.	Qty.
ASSRTL200000	2000 mm	2.1 m ³	550 kg	Pcs.
ASSRTL240000	2400 mm	2.6 m ³	660 kg	Pcs.
ASSRTL280000	2800 mm	3.0 m ³	765 kg	Pcs.

Other widths available on request.