

Manure and silage grab fork

- » Fully galvanized version
- » Thick-walled tine support with welded-in tapered bushings
- » Cylinder is positioned on top for strong grab arm and wide opening angle
- » Includes hydraulic couplers and hoses



For attachment to Euronorm

Art.no.	Version	Width	Tines	Weight approx.	Qty.
DSGFLM120000V	Two cylinders	1250 mm	7	290 kg	Pcs.
DSGFLM140000V	Two cylinders	1450 mm	8	310 kg	Pcs.
DSGFLM160000V	Two cylinders	1650 mm	9	330 kg	Pcs.
DSGFLM180000V	Two cylinders	1850 mm	10	350 kg	Pcs.
DSGFLM200000V	Two cylinders	2050 mm	11	370 kg	Pcs.
DSGFLM220000V	Two cylinders	2250 mm	12	390 kg	Pcs.

For attachment to farm, wheel or telescopic loaders

Art.no.	Version	Width	Tines	Weight approx.	Qty.
DSGHRT100000V	One cylinder	1050 mm	6	200 kg	Pcs.
DSGHRT120000V	One cylinder	1250 mm	7	220 kg	Pcs.
DSGHRT140000V	Two cylinders	1450 mm	8	320 kg	Pcs.
DSGHRT160000V	Two cylinders	1650 mm	9	340 kg	Pcs.
DSGHRT180000V	Two cylinders	1850 mm	10	360 kg	Pcs.
DSGHRT200000V	Two cylinders	2050 mm	11	380 kg	Pcs.
DSGHRT220000V	Two cylinders	2250 mm	12	400 kg	Pcs.



Illustration: two-cylinder version

