

Manure and silage grab bucket

- » Fully galvanized version
- » Cutting edge made of wear-resistant high-tensile steel 150 x 16 mm HB 450
- » Stable round-shaped bucket base
- » Cylinder is positioned on top for strong grab arm and wide opening angle
- » Left and right side walls bolted on
- » Includes hydraulic couplers and hoses



Wide variety of uses • stable and rugged
Telescopic, farm and wheel loader mountings available!
High-volume gripper
Better overloading onto high trailers
High grab angle

For attachment to Euronorm

Art.no.	Version	Width	Tines	Volume	Weight approx.	Qty.
DSSFLM120000V	Two cylinders	1250 mm	7	0.90 m ³	320 kg	Pcs.
DSSFLM140000V	Two cylinders	1450 mm	8	1.05 m ³	350 kg	Pcs.
DSSFLM160000V	Two cylinders	1650 mm	9	1.20 m ³	380 kg	Pcs.
DSSFLM180000V	Two cylinders	1850 mm	10	1.35 m ³	410 kg	Pcs.
DSSFLM200000V	Two cylinders	2050 mm	11	1.50 m ³	440 kg	Pcs.
DSSFLM240000V	Two cylinders	2250 mm	12	1.65 m ³	470 kg	Pcs.

For attachment to farm, wheel or telescopic loaders

Art.no.	Version	Width	Tines	Volume	Weight approx.	Qty.
DSSHRT160000V	Two cylinders	1650 mm	9	1.20 m ³	390 kg	Pcs.
DSSHRT180000V	Two cylinders	1850 mm	10	1.35 m ³	420 kg	Pcs.
DSSHRT200000V	Two cylinders	2050 mm	11	1.50 m ³	450 kg	Pcs.
DSSHRT240000V	Two cylinders	2250 mm	12	1.65 m ³	480 kg	Pcs.

