

Wireless Camera »Sparrow«

All in one system including Display and fastening components.

Technical details:

Monitor

- » LCD-size: 7"
- » Resolution: 1024 x 3 (RGB) x 600
- » Contrast: 800:1
- » Brightness: 500 cd/m²
- » Viewing angle: U: 70/D: 75, R/L: 75
- » Aspect ratio: 16:9
- » 4 channels
- » Operating frequency: 2412 - 2467 MHz
- » Transmission distance: 300 m
- » Decompressing format: H.264
- » Modulation: DSSS
- » Micro-SD/TF-card: Max. 128G
- » Delay: 200 ms
- » System format: PAL / NTSC
- » Power consumption: Max. 8W
- » Speaker: 1,5 W/8Ω
- » Operating temperature: -20 bis + 70°C, RH 90%
- » Storage temperature: -30 bis + 80°C, RH 90%

Camera

- » Imaging device: 1/4" CMOS HM1246
- » TV-system: PAL / NTSC
- » Pixle: 1280 (H) x 720 (V)
- » Scanning system: progressive scanning
- » Sync. system: internal
- » Minimum illuminatiion: 0.1 Lux (day), 0 Lux (with infrared)
- » Microphone: yes
- » Video output: 8 Bit YUV
- » AGC: auto
- » S/N relation: S/N (a-weighted) 101.6 dB
- » White balance: auto
- » BLC: auto
- » Operating frequency: 2412 MHz - 2467 MHz
- » Receiving sensitivity: -85 dBm
- » Video code: H.264
- » Transmission intervall: 300 M
- » Distribution spectrum: DSSS
- » Delay: 200 ms
- » HF-bit-rate: 12 Mbps
- » Operating temperature: -20°C to +70°C, RH 90% max.
- » Storage temperature: -30°C to +80°C, RH 90% max.



* Errors, technical changes reserved.