

»Fräsfix« milling drum – 2 oil motors

Can be mounted on any front, wheel or telescopic loader bucket

- » 1 x single-acting connection with return or 1 x double-acting connection required
- » Includes hydraulic couplers and hoses
- » Tilt adjustment via toothed wheel system



Illustration: milling drum Ø 350 mm, with high capacity bucket



Equipped with 2 oil motors
 Mills from 2.5 m³ to 6 m³
 of maize silage per minute
 Suitable for maize silage and CCM

»Fräsfix 350« milling drum – Ø 350 mm

Art.no.	Width	Capacity – Maize up to approx.	Recommended oil capacity – Maize approx.	Qty.
GRSFLM900015	2000 mm	2.5 m ³	At least 60 l	Pcs.
GRSFLM900016	2500 mm	3.0 m ³	At least 60 l	Pcs.
GRSFLM900018	3000 mm	3.5 m ³	At least 60 l	Pcs.

The milled quantity varies depending on the available oil capacity!

»Fräsfix 490« milling drum – Ø 490 mm

Art.no.	Width	Capacity – Maize up to approx.	Recommended oil capacity – Maize	Qty.
GRSFLM900019	2000 mm	5.0 m ³	At least 90 l	Pcs.
GRSFLM900017	2500 mm	5.5 m ³	At least 90 l	Pcs.
GRSFLM900026	3000 mm	6.0 m ³	At least 90 l	Pcs.



Illustration: milling drum Ø 490 mm, with high capacity bucket



Illustration: tilt adjustment via toothed wheel system



Illustration: protective cover for oil drive



Illustration: Hoses are routed internally, sturdy support pipes