

**Ölmotor BMT 630 / Ø 40 / Rundflansch Ø 210mm**

Art.Nr.: HMTXXX100365

		BMT-630						
		Δ Pressure (Bar)						
630cc		35	50	70	85	105	120	140
Flow LPM	3.8	250	380	510	640	755		
		5	4	4	3	2		
	7.5	260	395	535	670	795	925	1060
		12	13	13	10	10	8	6
	15	275	425	570	710	850	955	1065
		24	24	24	22	21	18	16
	30	295	450	605	755	925	1095	1270
		45	44	44	43	42	39	37
	45	295	450	610	765	920	1125	1330
		72	71	71	70	68	66	64
	61	285	445	605	760	915	1120	1325
		94	93	92	91	89	87	85
	76	280	440	595	755	915	1120	1325
		119	118	117	116	115	112	110
	91	265	430	585	745	905	1110	1320
		143	142	140	139	138	135	132
	106	255	415	575	735	895	1105	
		168	166	165	164	162	159	
	121	240	400	560	720	880		
		192	190	188	187	185		
136	220	380	540	700	855			
	216	214	213	212	210			

Torque 430 Nm  
Speed 137 RPM

**Performance data is typical with N68 anti-wear hydraulic oil at 50° C temperature. Actual data may vary slightly from unit to unit in production**

\*Irrtümer, technische Änderungen vorbehalten.