

Mix Master »Garant«

The »Garant« is the perfect mixer for all applications. You benefit from highest quality levels and robust construction, stemming from our extensive experience in the mixer segment.







Fig.: With hydraulic drive

Technical details:

- » Forklift mounting: Pocket dimensions: 152 mm x 72 mm
- » 3-blade, especially strong mixing springs (angle is adjustable)
- » Side wall scraper, discharge chute in the rear
- » Drive shaft with overload protection
- » Gearbox: 2-stage, translation ratio: 1:11
- » Pre-coated and 2 K-painted
- » Agitator has triple bearing
- » Extra heavy safety grid (agitator can be sealed off)

Features:

- » Adjustable side wall scraper
- » Lower link mounting Cat. II with 3 possible settings
- » Drum made of high-quality steel, star-shaped reinforced bottom
- » Mixing elements have long-lasting bearings, protected against dirt
- » Agitating tool made of wear-resistant high-tensile steel (adjustable laterally and downwards)
- » Water supply through hollow space on the safety grid
- » Heavy safety grid
- » Discharge slide in the rear (especially well sealed and smooth running)
- » Use of special materials (fine-grain steel)

Mix Master Garant 401 SS

Output per hour: approx. 7 cbm Power requirement: from 40 hp Filling diameter: 1100 mm

Mix Master Garant 602 SS

Output per hour: approx. 10 cbm Power requirement: from 50 hp Filling diameter: 1200 mm

Mix Master Garant 802 SS

Output per hour: approx. 12 cbm Power requirement: from 80 hp Filling diameter: 1500 mm

Mix Master Garant 1002 SS

Output per hour: approx. 15 cbm Power requirement: from 120 hp Filling diameter: 1800 mm

For attachment to three-point hitch ____

| Item No. | Designation | Mixing content | Net weight | δn |
|--------------|-----------------------------|----------------|------------|-----|
| MSSFLA040100 | Mix Master »Garant« 401 SS | 400 I | 430 kg | pcs |
| MSSFLA060200 | Mix Master »Garant« 602 SS | 600 I | 530 kg | pcs |
| MSSFLA080200 | Mix Master »Garant« 802 SS | 800 I | 630 kg | pcs |
| MSSFLA102000 | Mix Master »Garant« 1002 SS | 1000 | 750 kg | pcs |

For attachment to Euronorm, wheel or telescopic loaders . See . Se

Tél. +49 (0)8671/9600-0 · Fax +49 (0)8671/9600-701 · info@agro-center.de

| Item No. | Mounting type | QU |
|--------------|--|-----|
| MFAZUB401002 | Surcharge: Euronorm, wheel or telescopic loader mounting | pcs |

General accessories available for a surcharge

| Item No. | Designation | QU |
|--------------|---|-----|
| | | |
| MSSZUB401001 | Hydraulic drive with hoses for SS mixer | pcs |
| MSSZUB602102 | 11 kW electr. drive for 602 SS and 802 SS | pcs |
| MSSZUB102005 | 16.5 kW electr. drive for 1002 SS | pcs |
| MFAZUB400004 | Swivelling discharge chute (for Favorite 800/802SS/800FA and 100FA) | pcs |
| MSSZUB401006 | Filling bracket | pcs |
| MSSZUB401007 | Chassis (without licence) | pcs |
| MSSZUB401008 | Parking jacks extendible to 1200 mm | pcs |
| MFAZUB400001 | Bagging system | pcs |
| | | |