

## »Standard« heavy-duty bucket

With farm, wheel or telescopic loader mounting,  
 835 mm deep, 726 mm high

- » Fully galvanized version
- » Max. load capacity 3 tonnes
- » Optimum workmanship from a single piece with reinforcing profile

- » Material thicknesses: Shell plate 4 mm, side plate 5 mm, reinforced bottom
- » Heavy scrape rail made of wear-resistant high-tensile steel 150 x 16 mm HB 450
- » Tapered design ensures bulk materials slide off more easily



Illustration:  
 Manitou mounting



For attachment to farm loader

Art.no.	Width (bottom edge)	Content approx.	Qty.
SGSHFLO00007V	850 mm	0.35 m <sup>3</sup>	Pcs.
SGSHFLO00008V	950 mm	0.40 m <sup>3</sup>	Pcs.
SGSHFLO00009V	1050 mm	0.50 m <sup>3</sup>	Pcs.
SGSHFLO00000V	1200 mm	0.55 m <sup>3</sup>	Pcs.
SGSHFLO00001V	1500 mm	0.65 m <sup>3</sup>	Pcs.
SGSHFLO00002V	1800 mm	0.75 m <sup>3</sup>	Pcs.
SGSHFLO00003V	2000 mm	0.80 m <sup>3</sup>	Pcs.

For attachment to wheel or telescopic loaders

Art.no.	Width (bottom edge)	Content approx.	Qty.
SGSRTL000002V	1800 mm	0.75 m <sup>3</sup>	Pcs.
SGSRTL000003V	2000 mm	0.80 m <sup>3</sup>	Pcs.
SGSRTL000004V	2200 mm	0.85 m <sup>3</sup>	Pcs.
SGSRTL000005V	2400 mm	0.95 m <sup>3</sup>	Pcs.
SGSRTL000006V	2600 mm	1.05 m <sup>3</sup>	Pcs.
SGSRTL000007V	2800 mm	1.15 m <sup>3</sup>	Pcs.