

Tractor-hitched agitator

Fully galvanized version

For tilting connecting to the three-point hydraulics on the tractor-hitched agitator. Can be used with a reservoir opening of just 550 x 700 mm. Power required approx. 40 HP. Three-wing pressure blades 500 mm in diameter, without drive shaft.



Bearings are dirt resistant and feature long service life – optimally sealed
For open and closed reservoirs!
High-performance agitator blade
Standard blade diameter 500 mm



Illustration: hydraulically folding

Art.no.	Version	Length	Qty.
SRWFLI300000	Tractor-hitched agitator	3000 mm	Pcs.
SRWFLI400000	Tractor-hitched agitator	4000 mm	Pcs.
SRWFLI500000	Tractor-hitched agitator	5000 mm	Pcs.
SRWFLI600000	Tractor-hitched agitator	6000 mm	Pcs.
Accessories for a surcharge			
SRWFLI000550	Additional charge for hydraulically folding		Pcs.
GELLAM100050	Additional charge for drive shaft with »wide angle on one side« - heavy version		Pcs.
SRWFLI900050	Additional charge for agitator blade Ø 600 mm (for maximum stirring performance - tractor with over 100 HP required). Blade with Ø 600 mm is then delivered instead of Ø 500 mm		Pcs.