

## Combi »Open View« pallet fork

- » 2000 kg lifting capacity, guide rail 1500 mm wide
- » Especially rugged design
- » With 5 welded-in tapered bushing for trouble-free transport of round bales
- » Angularly milled guide rail in accordance with ISO 2328 (approx. 410 mm high), which makes adjusting the forks especially fast and easy (no tilting!)
- » Forged pallet forks (900 mm or 1200 mm) with spring adjustment and snap lock (guarantee forks will engage safely)
- » Forks: 80 x 35 mm, suspension FEM 2A, 2 tonnes lifting capacity per pair
- » Fully galvanized version



Very easy setup when using round bale tines due to available taper bushings (screw-on). With more or fewer tines depending on use.



»Open View« pallet fork with guard rail

Provides protection against slipping, for example with wood stacks, bales, steel sections and much more - can be retrofitted quickly and easily!



Art.no.	Product name	Other information	Weight approx.	Qty.
STGFLM000005V	»Open View« pallet fork, Euronorm;	With 900 mm forks	130 kg	Pcs.
STGFLM000007V	»Open View« pallet fork, Euronorm	With 1200 mm forks	145 kg	Pcs.

## Accessories for the »Open View« pallet fork

Art.no.	Product name	Weight approx.	Qty.
① STGFLM000850	Guard rail, loose <b>surcharge</b>	20 kg	Pcs.